

**T/Mon SLIM**



**T/Mon LNX**



<b>Target Application:</b>	Entry-level system, low capacity	<b>Full-Capacity Monitoring Solution</b>
<b>Supported Protocols (Input):</b> <i>(many require optional software modules)</i>	ASCII, Badger, Cordell, DCM, DCP, DCPf, DCPx, E2A, Felix, FX8800, Granger, Larse, Modbus, NEC, NTP, Ping, POP3, Pulsecom, SNMP, TABS, TBOS, Teltrac, T/MonNet, TL1, TRIP	ASCII, Badger, Cordell, DCM, DCP, DCPf, DCPx, E2A, Felix, FX8800, Granger, Larse, Modbus, NEC, NTP, Ping, POP3, Pulsecom, SNMP, TABS, TBOS, Teltrac, T/MonNet, TL1, TRIP
<b>Supported Protocols (Output):</b> <i>(many require optional software modules)</i>	ASCII, DCP, DCPf, DCPx, Pager, Ping, SNMP, TABS, TL1	ASCII, DCP, DCPf, DCPx, DCM, E2A, NEC, Pager, Ping, SMTP, SNMP, TABS, TBOS, Teltrac, T/MonNet, T/MonNT, TL1, TRIP, X.25
<b>Protocols (Remote Access):</b>	DTMF, Remote Access, T/GrafX, HTTP, HTTPS*	DTMF, Remote Access, T/MonGFX, HTTP, HTTPS*
<b>Web Interface:</b>	Old generation	<b>Web 2.0, Mobile Web</b>
<b>Simultaneous Users:</b>	5	<b>17</b>
<b>Monitoring Capacity:</b>	64 devices/10,000 alarm points	<b>1,000,000 alarm points</b>
<b>Dimensions:</b>	1.75" H (1RU) x 17" W x 12 "D	10.5" H (6RU) x 17" W x 14" D
<b>Mounting:</b>	19" or 23" rack	19" or 23" rack
<b>Power input:</b>	Dual -48VDC or 110VAC (with wall transformer)	Dual -48VDC or 110VAC
<b>Processor:</b>	400 MHz Eden	<b>2.4 Ghz quad core Xeon</b>
<b>Serial Ports:</b>	4 ports (serial, optional modem)	<b>16 ports</b>
<b>Serial Port Interfaces:</b>	RS-232, optional 33.6K Modem	RS-232, RS422/485, 202 modem, 1200 baud modem, 33.6K modem, FSK modem, PSK modem
<b>LAN Interface:</b>	Single 10/100	<b>Six 10/100/1000</b> <i>(Ideal for deployments with users, equipment, and email servers on different networks)</i>
<b>Console Access:</b>	RS232 direct (uses 1 of the 4), 33.6k dial-up (optional), LAN	RS232 direct, LAN, VGA/keyboard (optional)
<b>Hard Drive:</b>	Dual 40 GB IDE (5400 RPM)	<b>Dual 250 GB SATA (7200 RPM)</b>
<b>Hard Drive Redundancy:</b>	Auto periodic copies	<b>RAID-1</b>
<b>Fans:</b>	-	<b>3 + power supply fan</b>
<b>Removable Storage:</b>	-	<b>DVD/CD burner</b>
<b>Hardware Warranty:</b>	2 years	2 years
<b>Operating Temperature:</b>	32° to 95° F (0° to 35° C)	32° to 95° F (0° to 35° C)
<b>Operating Humidity:</b>	0%–95% (non-condensing)	0% to 90% (non-condensing)
<b>T/Mon Gold Plan Available:</b>	Yes	Yes
<b>Local SQL Support</b>	-	Optional software module
<b>Local Voice Generation</b>	-	Optional software module
<b>TCP/UDP Sockets</b>	50	<b>Up to 1000</b>
<b>RAM</b>	64 MB	<b>4 GB</b>